

CASE SEALER



CT 205 SDR CASE SEALER

Taping is the application of adhesive tape to, for example, a box or other surface. In the packaging industry, tape is often used to seal something, in most cases a box or package. In addition, tape is also used to bundle products, to mark products, to communicate a message or to prevent theft.

The ultimate goal of taping is to store and / or ship your products without damage, so that they arrive at your customer in perfect condition. Packaging tape or adhesive tape can be applied manually, with a table dispenser or by machine.

Machine with manual feed

The CT 205 SDR is an automatic case sealer suitable for PP or PVC tape from 25 mm to 75 mm.

The CT 205 SDR is particularly suitable for closing boxes of different lengths and widths that are randomly fed into the machine.

After filling the box, the operator folds the top cover and inserts the box manually. The tape machine automatically adjusts to the width and height of the box, after which the top and bottom are automatically closed with tape.

With the CT 205 SDR it is possible to professionally close hundreds of packages per day.



Options:

- 67 cm and 82 cm box width
- Wheels
- Extra transport / roller conveyors
- Direct printing / coding / labeling
- Other options on request



Technical data:	
Machine dimensions (H x W x D)	1782 x 1162 x 1064 mm
Closure	Top and bottom
Consumable	PP / PVC tape
Tape - outer diameter	360 mm (max)
Tape - core diameter	76 mm
Tape - width	25 - 75 mm
Package - length	min 200 mm - max ∞
Package - width	100 mm - 520 mm
Package - height	100 mm - 520 mm
Capacity	300 packages / hour
Transport	Side transport - 22 meter / minute
Air pressure	6 Bar
Power supply	380 V / 50 Hz / 3 phases
Weight	210 kg
	-





©2021 Cyklop International - All rights reserved - Specifications are subject to change without notice