



CST 940

STRETCH WRAPPER

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING

The pallet wrapper CST 940 can be easily integrated into an existing or new line. This film wrapper ensures that the total costs in your production line will decrease by using film with a high pre-stretch percentage.

The CST 940 is a maintenance-friendly machine, can wrap up to 40 pallets per hour and the film is easy to replace with the fast-loading system. A corner applicator can be added to the machine for extra strength.

Advantages

- Compact machine with limited installation dimensions
- Pre-stretch 150% - 200% - 250%
- Processes up to 40 pallets per hour
- Winding speed 16 rpm
- Very accessible foil trolley
- Ability to stack on the machine
- Standard equipped with roller conveyor in the machine

Options

- Acid protection
- For loads up to 3300 mm high
- For pallet weights up to 3500 kg
- Transport facility other than roller conveyor
- Adjusted transport height
- Pressure plate
- Corner applicator
- Seal unit with contrast plate
- Top sheet dispenser (inside)



> [Click here for a video of the CST 940](#) <

Technical data:	
Total power installed	3 kW - 5 kW with topsheet
Standard power supply	400 V - 50 Hz - 3 PH+N+G
Protection on electric system	IP 54
Max. pallet dimensions	1000 x 1200 mm
Standard pallet height	2400 mm
Max. pallet weight	1500 kg
Standard diameter	Ø 2150 mm
Transport height	450 - 500 mm
Max. rotation speed	16 rpm
Capacity per hour	Up to 40 pallets / hour
Operating pressure	6 Bar

Cyklop UK Limited
 Unit 2, Generation Business Park
 Barford Road
 St. Neots
 Cambridgeshire
 PE19 6YQ

+44 1480 216777
www.cyklop.co.uk
info@cyklop.co.uk

